


SATURNO IN

LED-Halbeinbaustrahler
9,3 W, CRI>90, Gehäuse aus
Aluminiumdruckguss, dreh-
und schwenkbar (350°/45°),
Entblendungsring wahlweise
gold oder schwarz, Driver
bitte separat bestellen



LED-recessed luminaire 9,3 W,
CRI>90, made of die-cast alu-
minium, adjustable (350°/45°),
anti glare ring optionally gold
or black, please order driver
separately



CODE	TYPE	COLOUR	LAMP	LUMEN	POWER SUPPLY	H
D559	SATURNO IN	white/black	1x9,3W LED 32° □ 2700K 500mA	860 lm	excl. driver	70 mm
D560	SATURNO IN	white/gold	1x9,3W LED 32° □ 2700K 500mA	860 lm	excl. driver	70 mm
D557	SATURNO IN	black/black	1x9,3W LED 32° □ 2700K 500mA	860 lm	excl. driver	70 mm
D558	SATURNO IN	black/gold	1x9,3W LED 32° □ 2700K 500mA	860 lm	excl. driver	70 mm

H = Einbautiefe / recessed depth

Driver siehe Seite 195 ff. / Driver see page 195 ff.

* Technische Informationen siehe Seite 189 / Lumenangaben sind Nominalwerte
* Technical information see page 189 / Lumen data are nominal data

