SAXO

SPECIFICATIONS		
MOUNTING		WALL RECESSED
POWER	[W]	2
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	185
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	=
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	92

POWER SUPPLY 220-240V AC 50/60 Hz [V] [A] LED-DRIVER **INCLUDED DIMMING** NO THROUGH-WIRING NO


MATERIAL **ALUMINUM INGRESS PROTECTION** IP54 PROTECTION CLASS Ш **NET WEIGHT** 0,34 [kg] **GROSS WEIGHT** [kg] 0,35

COLOUR (HOUSING) WHITE ~RAL9003 COLOUR (HOUSING) GREY ~RAL9006

CUT-OUT (FIXTURE) ø68 [mm] CUT-OUT (MOUNT. BOX) [mm] 72x72 RECESSED DEPTH 35 (fixture), 50 (mounting box) [mm]

*Luminous flux values are nominal LED data at a operating temperature of 25° C






OPTIONS / OPTIONAL ACCESSORIES




CUT OUT DIMENSIONS


FIXTURE DIMENSIONS

FIXTURE



















DLS LIGHTING

www.dlslighting.com

